



VX 200/4 C5

PORTABLE POWER

WELDING SETRangeWELDARC INTENS

PRODUCT ADVANTAGES

HONDA Professional Engine Generating set guaranteed 3 years Light storage box integrated Solid and high-performance equipment Auxiliary Single phase output

STAGE V (2016/1628 EU): This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range WELDARC INTENS

Welding sets which can be used on sites where there is no electricity.













VX 200/4 C5

GENERAL SPECIFICATIONS

Range	WELDARC INTENS
Frequency (Hz)	50 Hz
Max power (kW)	4
Max power (kVA)	4
Normal duty cycle 35% (A)	200
Intensif duty cycle 60% (A)	170
Stricking volts (V)	75
Rods diameter mini (mm)	1.6
Rods diameter maxi (mm)	4
Nominal voltage (V)	230
Number of Phase	Single phase
Fuel	Petrol
Tank (L)	6.1
75% cons. (I/h)	2.5
75% Autonomy (h)	2.4
Sound power level guaranteed LwA dB(A)	97
Acoustic pressure level @1m in dB(A)	83
Acoustic pressure level @7m in dB(A)	69

ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX390_C5
Engine Type	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	389
Oil system capacity including filters (I)	1 1

ALTERNATOR SPECIFICATION

Technology	Collar and brush
AVR Regulation	No
Indication of protection	IP 23
Insulation class	Н

PLUGS AND PANEL DESCRIPTIVE

2 230V 10/16A sockets - circuit breaker

DIMENSIONS AND WEIGHT

Length (cm)	88
Width (cm)	57
Height (cm)	55.5
Dry Weight (kg)	87

PACKAGING

Packaging type	Box / Pallet
Length (cm)	88
Width (cm)	58.5
Height (cm)	70
Weight (kg)	100
Pallet type	
Number of box by pallet	0
Pallet height (cm)	0
weight of the packaged Pallet (kg)	0

KOHLER.

VX 200/4 C5



ACCESSORIES SUPPLIED

Storage box User and maintenance manual

OPTIONS

R01	This set includes the hour meter and the differential circuit breaker
RKB2	Trolley kit for the generating sets superior to 6kW
R10	Welding kit includes 2 x 5 m of cable, 1 earth clip, 1 electrode holder, 1 hammer, 1 brush and 1 mask
3499231033203	R19 - Maintenance kit for Honda GX390 engines (except Alizé 6000E and Alizé 7500 TE)
RBH1	Box of 24 o.5L cans of oil or 20 1 L cans of oil (SAE 15W40)
RBH0-5	Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)
RH2	Cover for SDMO 's generating sets, welding sets and water pumps
RPQ	For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm² cable
RKD1	kit of two diferential removable adapters for domestic sockets. Schema for ground bonding with isolated neutral
3499231004555	GSC