



### BENEFITS

- Upto 100kVA
- Large internal fuel tank
- Integrated distribution unit
- Internal LED lighting
- Available with remote monitoring
- Available as hybrid package
- Reduced acoustic levels
- Completely self contained

### POPULAR FOR

- Construction sites
- Utilities sector
- Telecoms industry
- Highway applications
- Remote locations

### POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

### TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Inlet Temperature, of a barometric pressure of 100 kPa (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.

### GENERAL CHARACTERISTICS

Frequency (Hz)	50
Voltage (V)	400/230
Standard Control Panel	APM303

### POWER

Voltage	ESP		PRP		Standby Amps
	kWe	kVA	kWe	kVA	
220 TRI	35	44	32	40	115
220/127	35	44	32	40	115
415/240	35	44	32	40	61
400/230	35	44	32	40	64
380/220	35	44	32	40	67
200/115	35	44	32	40	127
240 TRI	35	44	32	40	106
230 TRI	35	44	32	40	110

### OVERALL DIMENSIONS

Length (mm)	2400
Width (mm)	3000
Height (mm)	2700
Dry weight (kg)	2850
Tank capacity (L)	1350

### CONTACT US

WB Power Services Ltd, Heanor Gate Road  
Heanor Gate Industrial Estate, Heanor  
Derbyshire DE75 7RJ

Email us at: [sales@wbpsltd.co.uk](mailto:sales@wbpsltd.co.uk)  
Call us 01159 444 422  
[www.wbpsltd.co.uk/hire](http://www.wbpsltd.co.uk/hire)



### GENERAL ENGINE DATA

Engine model	JOHN DEERE
Engine ref.	3029TFS29
Air inlet	Turbo
Cylinders arrangement	L
Number of cylinders	3
Displacement (C.I.)	2.91
Air coolant	
Bore (mm) x Stroke (mm)	106 x 110
Compression ratio	17.2 : 1
Speed (RPM)	1500
Pistons speed (m/s)	5.5
Maximum stand-by power at rated RPM (kW)	42
Frequency regulation (%)	+/- 2.5%
BMEP (bar)	10.44
Governor type	Mechanical

### COOLING SYSTEM

Radiator & Engine capacity (L)	16.1
Max water temperature (°C)	105
Outlet water temperature (°C)	93
Fan power (kW)	1.3
Fan air flow w/o restriction (m <sup>3</sup> /s)	1.86
Available restriction on air flow (mm Water Column)	20
Type of coolant	Glycol-Ethylene
Thermostat (°C)	82-94

### EXHAUST

Exhaust gas temperature (°C)	510
Exhaust gas flow (L/s)	105.60
Max. exhaust back pressure (mm EC)	625

### FUEL

Consumption @ 110% load (L/h)	10.80
Consumption @ 100% load (L/h)	9.80
Consumption @ 75% load (L/h)	7.50
Consumption @ 50% load (L/h)	5.30
Maximum fuel pump flow (L/h)	111

### OIL

Oil capacity (L)	6
Min. oil pressure (bar)	1
Max. oil pressure (bar)	5
Oil consumption 100% load (L/h)	0.0090
Carter oil capacity (L)	5.30

### HEAT BALANCE

Heat rejection to exhaust (kW)	38
Radiated heat to ambient (kW)	5
Heat rejection to coolant (kW)	28

### AIR INTAKE

Max. intake restriction (mm EC)	300
Intake air flow (L/s)	37.80

#### CONTACT US

WB Power Services Ltd, Heanor Gate Road  
Heanor Gate Industrial Estate, Heanor  
Derbyshire DE75 7RJ

Email us at: [sales@wbpsltd.co.uk](mailto:sales@wbpsltd.co.uk)  
Call us 01159 444 422  
[www.wbpsltd.co.uk/hire](http://www.wbpsltd.co.uk/hire)



GENERAL DATA	
Alternator ref.	ATO0540T
Number of Phase	Three phase
Power factor (Cos Phi)	0.8
Altitude (m)	0 to 1000
Overspeed (rpm)	2250
Number of pole	4
Capacity for maintaining short circuit at 3 in for 10 s	Yes
Insulation class	H
T° class, continuous 40°C	H / 125°K
T° class, standby 27°C	H / 163°K
AVR Regulation	Yes
Total Harmonic Distortion in no-load DHT (%)	3.7
Total Harmonic Distortion, on load DHT (%)	3.2
Wave form : NEMA=TIF	<45
Wave form : CEI=FHT	<2
Number of bearing	1
Coupling	Direct
Voltage regulation at established rating (+/- %)	+/- 1%
Recovery time (Delta U = 20% transient) (ms)	500
Indication of protection	IP 21
Technology	Without collar or brush

OTHER DATA	
Continuous Nominal Rating 40°C (kVA)	42
Standby Rating 27°C (kVA)	48
Efficiencies 100% of load (%)	88.6
Air flow (m3/s)	0.118
Short circuit ratio (Kcc)	0.8
Direct axis synchro reactance unsaturated (Xd) (%)	190
Quadra axis synchro reactance unsaturated (Xq) (%)	98
Open circuit time constant (T'do) (ms)	1320
Direct axis transient reactance saturated (X'd) (%)	14.3
Short circuit transient time constant (T'd) (ms)	61
Direct axis subtransient reactance saturated (X''d) (%)	10
Subtransient time constant (T''d) (ms)	15
Quadra axis subtransient reactance saturated (X''q) (%)	30.6
Subtransient time constant (T''q) (ms)	
Zero sequence reactance unsaturated (Xo) (%)	2.7
Negative sequence reactance saturated (X2) (%)	21.5
Armature time constant (Ta) (ms)	31
No load excitation current (io) (A)	0.7
Full load excitation current (ic) (A)	2.4
Full load excitation voltage (uc) (V)	25
Engine start (Delta U = 20% perm. or 50% trans.) (kVA)	107
Transient dip (4/4 load) - PF : 0.8 AR (%)	15.5
No load losses (W)	959.68
Heat rejection (W)	4375
Unbalanced load acceptance ratio (%)	

### APM303, comprehensive and simple

The APM303 is a versatile unit which can be operated in manual or automatic mode. Equipped with an LCD screen, the user-friendly APM303 offers high-quality basic functions to guarantee simple, reliable operation and supervision of your generating set. It offers the following features:



**Measurements:** phase-to-neutral and phase-to-phase voltages, active power currents, effective power, power factors, Kw/h energy meter Fuel, oil pressure and coolant temperature levels

**Supervision:** Modbus RTU communication on RS485

**Reports:** 2 configurable reports

**Safety features:**

Overspeed, oil pressure

Coolant temperatures

Minimum and maximum voltage

Minimum and maximum frequency

Maximum current

Maximum active power

Phase sequence

**Traceability:**

Stack of 12 stored events For further information, please refer to the data sheet for the APM303.